

12/02/99

JOS35 U.S. PRO

UTILITY PATENT APPLICATION TRANSMITTAL

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Attorney Docket No. 862.3158

First Named Inventor or Application Identifier

SHOICHI YAMAGUCHI

Express Mail Label No.

OLD S/N 159-1

891234/60

12/02/99

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

1. ☐ Fee Transmittal Form
(Submit an original, and a duplicate for fee processing)2. ☒ Specification Total Pages 223. ☒ Drawing(s) (35 USC 113) Total Sheets 24. ☒ Oath or Declaration Total Pages 1a. ☒ Newly executed (original or copy)b. ☐ Unexecuted for information purposesc. ☐ Copy from a prior application (37 CFR 1.63(d))
(for continuation/divisional with Box 17 completed)
[Note Box 5 below]i. ☐ DELETION OF INVENTOR(S)Signed Statement attached deleting inventor(s)
named in the prior application, see 37 CFR
1.63(d)(2) and 1.33(b).5. ☐ Incorporation By Reference (useable if Box 4c is checked)
The entire disclosure of the prior application, from which a copy of the
oath or declaration is supplied under Box 4c, is considered as being
part of the disclosure of the accompanying application and is hereby
incorporated by reference therein.

ADDRESS TO:

Assistant Commissioner for Patents
Box Patent Application
Washington, DC 202316. ☐ Microfiche Computer Program (Appendix)7. Nucleotide and/or Amino Acid Sequence Submission
(if applicable, all necessary)a. ☐ Computer Readable Copyb. ☐ Paper Copy (identical to computer copy)c. ☐ Statement verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

8. ☒ Assignment Papers (cover sheet & document(s))9. ☐ 37 CFR 3.73(b) Statement ☐ Power of Attorney
(when there is an assignee)10. ☐ English Translation Document (if applicable)11. ☐ Information Disclosure Statement (IDS)/PTO-1449 ☐ Copies of IDS
Citations12. ☐ Preliminary Amendment13. ☒ Return Receipt Postcard (MPEP 503)
(Should be specifically itemized)14. ☐ Small Entity Statement(s) ☐ Statement filed in prior application
Status still proper and desired15. ☐ Certified Copy of Priority Document(s)
(if foreign priority is claimed)16. ☐ Other: _____

17. If a CONTINUING APPLICATION, check appropriate box and supply the requisite information:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No. ____/____

18. CORRESPONDENCE ADDRESS

☒ Customer Number or Bar Code Label05514
(Insert Customer No. or Attach bar code label here)or ☐ Correspondence address below

NAME

Address

City

Country

State

Telephone

Zip Code

Fax

CLAIMS	(1) FOR	(2) NUMBER FILED	(3) NUMBER EXTRA	(4) RATE	(5) CALCULATIONS
	TOTAL CLAIMS (37 CFR 1.16(c))	16-20 =	0	X \$ 18.00 =	\$ 0.00
	INDEPENDENT CLAIMS (37 cfr 1.16(b))	2-3 =	0	X \$ 78.00 =	\$ 0.00
	MULTIPLE DEPENDENT CLAIMS (if applicable) (37 CFR 1.16(d))			\$260.00 =	\$ 0.00
				BASIC FEE (37 CFR 1.16(a))	\$760.00
			Total of above Calculations =		\$760.00
Reduction by 50% for filing by small entity (Note 37 CFR 1.9, 1.27, 1.28).					
				TOTAL =	\$760.00

19. Small entity status

- a. ☐ A Small entity statement is enclosed
- b. ☐ A small entity statement was filed in the prior nonprovisional application and such status is still proper and desired.
- c. ☐ Is no longer claimed.

20. ☒ A check in the amount of \$ 760.00 to cover the filing fee is enclosed.

21. ☒ A check in the amount of \$ 40.00 to cover the recordal fee is enclosed.


22. The Commissioner is hereby authorized to credit overpayments or charge the following fees to Deposit Account No. 06-1205:

- a. ☒ Fees required under 37 CFR 1.16.
- b. ☒ Fees required under 37 CFR 1.17.
- c. ☐ Fees required under 37 CFR 1.18.

SIGNATURE OF APPLICANT, ATTORNEY, OR AGENT REQUIRED

NAME Leonard P. Diana (Reg. No. 29,296)

SIGNATURE



DATE

December 1, 1999

TITLE OF THE INVENTION

COMMUNICATION APPARATUS AND METHOD

5 BACKGROUND OF THE INVENTION

This invention relates to a communication apparatus and method capable of transmitting information to another party by facsimile communication or
10 communication using electronic mail.

The increasing use of electronic mail over the Internet in recent years has led to the appearance even of facsimile machines that can be connected to the Internet or to a LAN to make possible the sending and
15 receiving of electronic mail.

Maintaining the security of document information sent and received by facsimile is a concern. Since facsimile communication via an ordinary public telephone network involves a direct one-on-one connection between
20 the communicating parties via the network, the degree of security in terms of the communication path is comparatively high. However, once the faxed documents have been received by the facsimile machine on the receiving side, the received information is, as a rule,
25 printed out by the receiving facsimile machine. The degree of security on the receiving side, therefore, is

comparatively low.

A solution has been to use a confidential message-box function to assure secrecy. This function involves the sending side notifying the receiving side of the fact that a confidential transmission is to be made, accumulating the received documents in a confidential message box on the receiving side and outputting the documents on the receiving side only when a correct secret number has been entered.

Conversely, with regard to electronic mail sent over the Internet, mail arrives at the communicating party on the receiving side via a number of unspecified routers and mail servers, etc., that constitute the network, and ASCII character codes are exchanged over this communication path as is. The degree of security in this case, therefore, is comparatively low. However, because an electronic mail scheme comes equipped with a mailbox function, the degree of security of received documents once they have arrived at the receiving party is high.

Thus, the security of documents communicated by facsimile differs greatly from that communicated by electronic mail. In order to assure an equivalent degree of security for both kinds of communication with the conventional apparatus of the type described above, the user must perform different communication operations

upon being sufficiently aware of the difference in security of both kinds of communication.

SUMMARY OF THE INVENTION

5

Accordingly, an object of the present invention is to provide a communication apparatus capable of affording an equivalent level of security for both facsimile transmission and electronic mail without the user needing to be aware of the difference between facsimile transmission and electronic mail.

Another object of the present invention is to afford an equivalent level of security for both facsimile transmission and electronic mail in a case where the user indicates the need for security at the time of document transmission, wherein image data is encrypted if a document is transmitted by an electronic mail function and, if possible, a private security function is used if a document is transmitted by facsimile.

According to the present invention, the foregoing objects are attained by providing a communication apparatus comprising: facsimile communication means for transmitting transmission information to a destination apparatus in accordance with facsimile communication specifications; electronic-mail communication means for

transmitting transmission information to a destination
apparatus in accordance with electronic-mail
specifications; communication designating means for
causing transmission of the transmission information by
5 selecting either the facsimile communication means or
the electronic-mail communication means; and security
designating means for designating whether the
transmission information is confidential information;
wherein if the transmission information has been
10 designated as being confidential information by the
security designating means, the facsimile communication
means transmits the transmission information to the
destination apparatus as is by facsimile transmission
when the facsimile communication means has been
15 designated by the communication designating means, and
the electronic-mail communication means encrypts the
transmission information and then sends it to the
destination apparatus by electronic mail when the
electronic-mail communication means has been designated
20 by the communication designating means.

By way of example, if the destination apparatus
possesses a private security function, the facsimile
communication means transmits the transmission
information to a mailbox utilizing this private security
25 function if the transmission information has been
designated as being confidential information by the

security designating means.

Further, the transmission information is, e.g., document information obtained by reading a document.

Other features and advantages of the present
5 invention will be apparent from the following description taken in conjunction with the accompanying drawings, in which like reference characters designate the same or similar parts throughout the figures thereof.

10 BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a block diagram illustrating an embodiment according to the present invention; and

15 Fig. 2 is a flowchart illustrating transmission processing according to this embodiment.

DESCRIPTION OF THE PREFERRED EMBODIMENT

20 A preferred embodiment of the present invention will now be described in detail with reference to the drawings.

Fig. 1 is a block diagram illustrating the construction of an image-information communication
25 apparatus according to an embodiment of the present invention.

As shown in Fig. 1, the apparatus includes a CPU 101 for exercising overall control of the apparatus; a ROM 102 for storing the control program; a RAM 103 for storing program control variables and the like; an image
5 memory 104, which is constituted by a DRAM or the like, for storing information such as data that is sent and received.

The apparatus further includes an image reader 105, which includes such components as an image sensor and a
10 document transport mechanism, for optically reading a document and converting it to electrical image data, and a control panel 106 for inputting various operating commands and having an external display unit capable of being implemented by an LCD, LEDs or the like. The
15 external control unit displays the status of the apparatus and the results of commands and thus interfaces the operator.

The apparatus further includes an image recording unit (printer) 107 for printing a received image or file
20 data on printing paper; a LAN interface 108 which exercises control for connecting the apparatus to a LAN 300; and an image format converter 109 for subjecting an image to various format conversions.

The apparatus further includes an electronic-mail
25 format converter 110 for converting text data and image data to an electronic-mail format; an electronic-mail

format analyzer 111 for analyzing the content of data having an electronic-mail format; a public-network interface 112 used to connect the apparatus to a facsimile machine 250 of another party via a public network 200; and an encryption processor 113 for encrypting electronic-mail transmission information under the control of the CPU 101.

The public network 200, which is a public facsimile communications network, is capable of being connected to the other communication apparatus 250 via a public-network interface and can transmit information to the other communication apparatus 250 in accordance with facsimile communication specifications. It should be noted that the other communication apparatus 250 capable of being connected to the public network 200 has a mailbox 260.

The LAN 300 is capable of sending and receiving electronic mail. The apparatus according to this embodiment is adapted so that information can be transmitted between this apparatus and another communication apparatus 350 by electronic mail via the LAN interface 108. Numeral 400 denotes a mail server that is capable of accumulating electronic mail.

Reference will be had to Fig. 2 to describe transmission processing for reading a document image by the image reader 105 and transmitting the image to a

desired destination in accordance with the embodiment having the construction set forth above. Fig. 2 is a flowchart illustrating transmission processing according to this embodiment.

5 A sending party who wishes to transmit a document image using the apparatus of this embodiment first places the document in the image reader 105 and uses the control panel 106 to enter various indications necessary for transmission (step S101). These indications include
10 an indication of the destination to which data is to be communicated, an indication as to whether transmission is a confidential transmission, and an indication of the transmission method, i.e., whether transmission is by facsimile or electronic mail.

15 The sending party commands transmission by entering a command from the control panel 106 to start the scanning of a document. Upon sensing the transmission command, the CPU 101 sends the read document information (transmission information) to the image format converter
20 109 at step S102. The image format converter 109 encodes this information in accordance with a data format in a case where facsimile communication compliant with the G3 standard, for example, is carried out. The coded transmission information is stored in the image
25 memory 104 at step S103. For example, all documents are stored in the image memory 104.

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25

If the scanning of all documents is finished, then, at step S104, the input state of a key that is for commanding a confidential transmission from the control panel 106 at step 101 is sensed and it is determined whether the command indicates confidential transmission. According to this embodiment, if the command indicates a confidential transmission, it is judged that security needs to be assured at the time of document transmission and data transmission in which security is assured is carried out.

If it is determined at step S104 that the transmission is not confidential, then control proceeds to step S105 and ordinary transmission is performed in accordance with the specified transmission method.

15
16
17
18
19
20
21
22
23
24
25

More specifically, if a confidential transmission has not been designated, then, at step S105, it is determined whether the designation of the communication method from the control panel 106 is selection of facsimile transmission or selection of transmission by electronic mail. Control proceeds to step S106 in a case where facsimile communication has been selected to transmit data to the transmission destination.

In this case, a telephone number is specified as the destination identifying information. As a result, the CPU 101 starts up the public-network interface 112 to call the public network 200, sends the public network

200 a telephone number signal such as a dial signal or MF signal corresponding to the specified destination telephone number and calls the apparatus of the other communicating party to thereby form a communication path to the destination apparatus. Next, at step S107, the document image data that has been stored in the image memory 104 is transmitted to the destination apparatus by data communication (facsimile communication). Processing is exited when all image data has been transmitted.

If it is found at step S105 that the designation of the transmission method from the control panel 106 is selection of transmission by electronic mail and an electronic mail address has been specified as the destination of communication, then control proceeds to step S110 to start up the image format converter 109. The latter converts the read document information to an image format such as the TIFF-F format. The converted data is then applied to the electronic-mail format converter 110, which applies coding conforming to electronic mail, such as BASE64, to thereby convert the data to information capable of being transmitted as electronic mail.

Next, at step S111, the LAN interface 108 is activated to transmit the information, along with the mail address of the destination and the mail address of

the local apparatus, to the other communication
apparatus 350 via the LAN 300. More specifically, the
transmission data is transferred from the apparatus of
this embodiment to the mail server 400 via the LAN 300,
5 and the other communication apparatus 350 at the
destination accepts the data from the mail server 400.

If it is determined at step S104 that the control
panel 106 has issued a confidential-transmission
command, control proceeds to step S108, where it is
10 determined whether the method of transmission selected
at the control panel 106 is transmission based upon
electronic mail or facsimile transmission using the
public network 200.

If transmission by electronic mail has been
15 selected, control proceeds to step S109, where the
encryption processor 113 is activated to encrypt the
transmission information that has been stored in the
image memory 104. This is followed by the processing
from step S110 onward, at which the encrypted
20 information is converted to an image format such as the
TIFF-F format by the image format converter 109, then
converted to an electronic-mail format by the
electronic-mail format converter 110 and transferred to
the mail server 400 via the LAN interface 108 and LAN
25 300.

In the example described above, first encryption

processing is executed at step S109 and then a conversion is made to the image format such as TIFF-F. However, the mode of the invention is not limited to the above-described example. By way of example, control may
5 be performed in such a manner that image data is encrypted after a conversion is made to the image format such as TIFF-F. Furthermore, encryption may be performed after a conversion is made to the image format such as TIFF-F. In other words, security can be assured
10 if encryption is performed by the time of transmission to the LAN 300.

If it is found at step S108 that facsimile communication has been selected as the communication method, control proceeds to step S112. Here, through
15 control similar to that of step S106, the public-network interface 112 is started up to call the public network 200, a telephone number signal or the like corresponding to the destination telephone number specified by the control panel 106 is sent to the public network 200 and
20 the desired destination facsimile apparatus, e.g., the other communication apparatus 250, is called to thereby form a communication path to the destination apparatus.

Next, at step S113, processing which precedes well-known facsimile communication processing is executed to
25 determine whether the other communication apparatus supports a private security function. If the other

communication apparatus does not support a private security function, control proceeds to step S107. Here, in a manner similar to that of the usual case described above, the document image data that has been stored in the image memory 104 is sent to the destination apparatus as is and the latter executes processing similar to the usual facsimile communication processing.

If it is found at step S113 that the other apparatus does have a private security function, on the other hand, then control proceeds to step S114. Here the other communication apparatus 250 is notified of the fact that the communication to follow will be a confidential transmission and then the transmission data that has been stored in the image memory 104 is transmitted to the other communication apparatus 250 at the destination via the public-network interface 112 and public network 200. The other communication apparatus 250 performs confidential reception, such as by storing the received information in the mailbox 260, and executes reception processing in accordance with a method that enables security to be assured.

The example described above relates to a case where the apparatus of the embodiment is provided on the transmitting side. However, the apparatus can operate also as an apparatus provided on the receiving side. In such case encrypted data that has been encrypted and

sent when security is required is applied to the encryption processor 113. The latter decodes the data by decryption.

Facsimile data that has been sent by confidential
5 transmission may be stored in a designated mailbox and the designated recipient may be informed of the fact that confidential reception took place.

Thus, in accordance with the embodiment described above, there are provided means for transmitting a
10 document by facsimile, means for transmitting a document as by electronic mail, means for designating which of these two means is to transmit a document, and means for designating whether a document is to be kept confidential. As a result, when confidentiality of a
15 document is designated and transmission by electronic mail is designated at the time of transmission, the document can be transmitted upon being encrypted. Thus, a document can be sent and received safely by an electronic-mail function even in applications where a
20 high level of security is required. Furthermore, facsimile communication can be carried out as well and in this case also a private security function can be used satisfactorily to maintain an equivalent level of security.

25 For example, if an indication for assuring security is made when document information is transmitted, image

data is encrypted in a case where the document is transmitted by an electronic-mail function and the above-mentioned private security function is used in a case where the document is transmitted by facsimile.

5 Thus there can be provided a communication apparatus that is capable of affording an equivalent level of security without the user needing to be aware of the difference between a facsimile transmission and an electronic-mail transmission.

10 The present invention can be applied to a system constituted by a plurality of devices (e.g., a host computer, interface, reader, printer, etc.) or to an apparatus comprising a single device (e.g., a copier or facsimile machine, etc.).

15 Furthermore, it goes without saying that the object of the invention is attained by supplying a storage medium storing the program codes of the software for performing the functions of the foregoing embodiment to a system or an apparatus, reading the program codes with
20 a computer (e.g., a CPU or MPU) of the system or apparatus from the storage medium, and then executing the program codes.

In this case, the program codes read from the storage medium implement the novel functions of the
25 invention, and the storage medium storing the program codes constitutes the invention.

Further, the storage medium, such as a floppy disk, hard disk, optical disk, magneto-optical disk, CD-ROM, CD-R, magnetic tape, non-volatile type memory card or ROM can be used to provide the program codes.

5 Furthermore, besides the case where the aforesaid functions according to the embodiment are implemented by executing the program codes read by a computer, it goes without saying that the present invention covers a case where an operating system or the like running on the
10 computer performs a part of or the entire process in accordance with the designation of program codes and implements the functions according to the embodiments.

It goes without saying that the present invention further covers a case where, after the program codes
15 read from the storage medium are written in a function expansion board inserted into the computer or in a memory provided in a function expansion unit connected to the computer, a CPU or the like contained in the function expansion board or function expansion unit
20 performs a part of or the entire process in accordance with the designation of program codes and implements the function of the above embodiment.

In a case where the present invention is applied to the above-mentioned storage medium, program code
25 corresponding to the flowchart of Fig. 2 described earlier would be stored on the storage medium.

Thus, in accordance with the present invention, as described above, there can be provided a communication apparatus that is capable of affording an equivalent level of security without the user needing to be aware
5 of the difference between a facsimile transmission and an electronic-mail transmission. Specifically, if an indication for assuring security is made when a document is transmitted, image data is encrypted in a case where the document is transmitted by an electronic-mail
10 function, and the above-mentioned private security function is used, if possible, in a case where the document is transmitted by facsimile.

As many apparently widely different embodiments of the present invention can be made without departing from
15 the spirit and scope thereof, it is to be understood that the invention is not limited to the specific embodiments thereof except as defined in the appended claims.

WHAT IS CLAIMED IS:

1. A communication apparatus comprising:

facsimile communication means for transmitting
transmission information to a destination apparatus in

5 accordance with facsimile communication specifications;

electronic-mail communication means for
transmitting transmission information to a destination
apparatus in accordance with electronic-mail
specifications;

10 communication designating means for causing
transmission of the transmission information by
selecting either said facsimile communication means or
said electronic-mail communication means; and

security designating means for designating whether
15 the transmission information is confidential
information;

wherein if the transmission information has been
designated as being confidential information by said
security designating means, said facsimile communication
20 means transmits the transmission information to the
destination apparatus as is by facsimile transmission
when said facsimile communication means has been
designated by said communication designating means, and
said electronic-mail communication means encrypts the
25 transmission information and then sends it to the
destination apparatus by electronic mail when said

electronic-mail communication means has been designated by said communication designating means.

2. A computer program sequence for implementing functions described in claim 1.

5 3. A computer-readable recording medium storing a computer program for implementing functions described in claim 1.

4. The apparatus according to claim 1, wherein if the destination apparatus possesses a private security
10 function, said facsimile communication means transmits the transmission information by confidential communication utilizing this private security function when the transmission information has been designated as being confidential information by said security
15 designating means.

5. The apparatus according to claim 1, wherein when the transmission information has been designated as being confidential information by said security designating means, said facsimile communication means checks to
20 determine whether the destination apparatus possesses a private security function by inquiring as to whether the destination apparatus possesses the private security function when a communication path to the destination apparatus is formed.

25 6. A computer program sequence for implementing functions described in claim 5.

7. A computer-readable recording medium storing a computer program for implementing functions described in claim 5.

8. The apparatus according to claim 1, wherein said security designating means makes a determination that the transmission information is confidential information when the fact that transmission is by confidential communication is designated.

9. The apparatus according to claim 1, wherein the transmission information is document information that has been obtained by reading a document.

10. A communication method in a communication apparatus capable of selectively executing facsimile communication for transmitting transmission information to a destination apparatus in accordance with facsimile communication specifications and electronic-mail communication for transmitting transmission information to a destination apparatus in accordance with electronic-mail specifications, said method comprising the following steps in a case where the transmission information is transmitted to a destination apparatus as confidential information:

transmitting the transmission information to the destination apparatus as is by facsimile transmission when communication is performed in accordance with facsimile communication; and

encrypting the transmission information and then sending it to the destination apparatus by electronic mail when communication is performed in accordance with electronic-mail communication.

5 11. A computer program sequence for implementing functions described in claim 10.

12. A computer-readable recording medium storing a computer program for implementing functions described in claim 10.

10 13. The method according to claim 10, wherein if the destination apparatus possesses a private security function in a case where facsimile communication is performed, the transmission information is transmitted to a mailbox that utilizes this private security
15 function when the transmission information is transmitted as confidential information.

14. A computer program sequence for implementing functions described in claim 13.

15 15. A computer-readable recording medium storing a computer program for implementing functions described in claim 13.

20 16. The method according to claim 13, wherein the transmission information is document information that has been obtained by reading a document.

ABSTRACT OF THE DISCLOSURE

Provided is a communication apparatus capable of
affording an equivalent level of security for both
5 facsimile transmission and electronic mail without the
user needing to be aware of the difference between
facsimile transmission and electronic mail. When
document information is designated as being confidential
("YES" at S104 in Fig. 2) and transmission by E-mail is
10 specified (S108, S109) at the time of a transmission,
the document is encrypted and transmitted (S109 - S111).
When transmission by facsimile communication is
specified (S108 - S112), on the other hand, the document
is transmitted utilizing a private security function
15 (S114).

FIG. 1





FIG. 2



COMBINED DECLARATION AND POWER OF ATTORNEY
FOR PATENT APPLICATION

(Page 1)

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name;

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

COMMUNICATION APPARATUS AND METHOD

the specification of which [X] is attached hereto. [] was filed on _____
as United States Application No. or PCT International Application No. _____
and was amended on _____ (if applicable).

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR §1.56.

I hereby claim foreign priority benefits under 35 U.S.C. §119(a)-(d) or §365(b), of any foreign application(s) for patent or inventor's certificate, or §365(a) of any PCT international application which designates at least one country other than the United States, listed below and have also identified below any foreign application for patent or inventor's certificate, or PCT international application having a filing date before that of the application on which priority is claimed:

<u>Country</u>	<u>Application No.</u>	<u>Filed (Day/Mo./Yr.)</u>	<u>(Yes/No)</u> <u>Priority Claimed</u>
JAPAN	10-350548	09/12/1998	Yes

I hereby appoint the practitioners associated with the firm and customer number provided below to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith, and direct that all correspondence be addressed to the address associated with that Customer Number:

FITZPATRICK, CELLA, HARPER & SCINTO
Customer Number: 05514

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full Name of Sole or First Inventor Shoichi YAMAGUCHI
Inventor's signature Shoichi Yamaguchi
Date November 20, 1999 Citizen/Subject of Japan
Residence 51-11-901, Tobehoncho, Nishi-ku, Yokohama-shi,
Kanagawa-ken, Japan
Post Office Address c/o CANON KABUSHIKI KAISHA,
30-2, Shimomaruko 3-chome, Ohta-ku, Tokyo, Japan
F511/A601948/ald